

Master Keyway

A Dia. Max. Over Knurl

RFI Fingers

Blue Color Band

290 Min. Full Thread

H Accessory Thread

3 Teeth Equally Spaced 120° Apart

B Dia. Max. Grommet

.190 Grommet Extension

Fully Coupled Indicators

320 Min.

1.420 Max.

INSERT ARRANGEMENT 24-31





NUMBER OF CONTACTS 31

CONTACT SIZE

○ ● ◐

20 16 12

1. PART NO: MS3475W24-31S
2. SHELL TYPE: RFI SHIELDED PLUG.
3. OPERATING TEMPERATURE: -55°C TO 200°C
4. ENDURANCE: 500 OPERATIONS.
5. VIBRATION: 50- 2000Hz, 4.172g PEAK LEVEL.
6. SHOCK: 300G -3ms IN THREE AXIS.
7. CLASS AND PLATING: OLIVE GREEN CADMIUM.
8. APPLICABLE STANDARDS: MIL-C 26482 SERIES II.
9. FIRE SAFETY PERFORMANCE : EN45545-2 (HL3) .

PRODUCT		MUMBAI METRO CARS L2 & L7			
REF DRG					
MATERIAL					
HEAT TREAT.		APPD	SYLAJA V		25.01.20
SURFACE TREAT.		REVD	K NAGARAJ		25.01.20
TITLE Connector plug (MS3475W24-31S)		CHKD	K NAGARAJ		25.01.20
		DRWN	PALLAVI		25.01.20
		SCALE		SHEET	Wt.(Kg)
		NTS		1 OF 1	0
		DRG No.		ALT 	
 BEM BEML LIMITED <small>NEW FRONTIERS · NEW DREAMS</small>		525-21131			