

KIT LIST - 412ZZC0084 (12 ITEMS)

Sl.No	P/ No	Description	Qty/ Kit	Material Specification
1	172.64.001	SPRING	3	LM: Wire II A - 2,5, according to GOST 9389-75 M: Spring wire CI 2,5, according to PN-71/M-80057 ST: see specification 172.000
2	172.64.045-1	SPRING	3	LM: wire IIA-1,8 according to GOST 9389-75 M: spring wire C I 1,8 according to PN-71/M-80057 ST: see specification 172.000
3	54.20.064 OR B40.20.064	SPRING	3	spring wire B-1,2 according to DIN 2076L:1984 (DIN 17223-1:1984).
4	172.31.268	SPRING	3	LM: wire 1-N-12H18N9T according to GOST 18143-72 M: round wire C 2 -1,0h12-1H18N9T according to BN-82/0654-01
5	172.31.271-1	SPRING	3	LM: wire 2,5-N-12H18N9T according to GOST 18143-72 M: round wire 2,5h12-1H18N9T according to BN-82/0654-01
6	432.31.224	SPRING	3	LM: steel 2 GOST19904-74 12H18N10T GOST5582-75 M: steel X6CrNiTi18-10+AT PN-EN 10088-2;
7	432.36.144	SPRING	3	LM: wire II A-3 according to GOST 9389-75 M: spring wire B II 3,0 according to PN-71/M-80057; Alt M: spring wire B-3,0 according to DIN 2076:1984 (DIN 17223-1:1984) or spring wire SM-3,0 or DM-3,0 PN-EN 10270-1 ST: see specification 172.000
8	172.41.137	Spring	3	LM: wire II-A-P-0,5, GOST 9389-75 (Y); M: spring wire B-I-0,5, PN-71/M-80057 (Y); Alt. M:spring wire B-0,5, DIN 2076:1984 (DIN 17223-1:1984) or spring wire BII0,5, PN-71/M-80057 (Y); ST: see specification 172.000 (PN);
9	54.41.019-2 or B40.41.019-2	Spring	8	LM: wire 51HFA-W-HN-4,0, GOST 14963-78 (Y); M: round bar CSP 4,0-h11-50HF-M, PN-H-93234:1997 (N); Alt. M: round bar CSP-4,0-h11 made of steel 50HFA-M; 50HFPr-M; 50HFAPr-M; or wire with surface grade A and B, GOST 14963-78. It is permissible to make from round bar CS-4,0-h11-50HF-M or 50HFA-M; 50HFPr; 50HFPr-M, PN-H-93234:1997; Q&T: HRC 42 to 50; ST: see specification 172.000 (PN);
10	54.34.148 OR B40.34.148	SPRING	3	SPRING WIRE B II 1,6 PN-71/M-80057
11	172.61.064	SPRING	3	SPRING WIRE B I 1,4 PN-71/M-80057
12	54.22.011 OR B40.22.011	SPRING	3	SPRING WIRE C II 1,2 PN-71/M-80057