

KIT LIST- 412ZZC0668 (38 ITEMS)

SL No	Part No	Description	Qty/ Kit	Material Specification
1	B71.29.1522	Spring	3	spring wire B-2,0 according to DIN 2076:1984/ (DIN 17223-1:1984)
2	B40.30.140-1	Ring	4	spring wire B-3,0 according to DIN 2076:1984 (DIN 17223-1:1984)
3	B40.29.052	Lock spring	4	spring wire B-1,4 according to DIN 2076:1984 (DIN 17223-1:1984)
4	54.08.068 or B40.08.068	Spring	3	D-1,4 according to DIN 2076:1984 (DIN 17223-1:1984)
5	54.30.885-1 or B40.30.885-1	Spring	10	spring wire B-1,6; according to DIN 2076:1984/ (DIN 17223-1:1984)
6	54.83.401 or D40.83.401	Spring	4	spring wire B-1,2; D-1,2 acc. to DIN 2076: 1984 (DIN 17223-1: 1984)
7	54.83.092-2	Spring	4	wire 50HFA-W-HN-3,0 according to GOST 14963-78
8	54.29.381-2 or B40.29.381-2	Spring	4	spring wire B-1,6; according to DIN 2076:1984/ (DIN 17223-1:1984)
9	155.29.2225-1	Spring	4	spring wire B-4,0 according to DIN 2076:1984 (DIN 17223-1:1984)
10	B71.29.406-2	Spring	4	spring wire B-5,0 according to DIN 2076:1984 (DIN 17223-1:1984)
11	B40.32.353	Spring	4	spring wire B-2,0 according to DIN 2076:1984 (DIN 17223-1:1984)
12	B40.29.052	Lock Spring	2	spring wire B-1,4 according to DIN 2076:1984 (DIN 17223-1:1984)
13	B40.08.068	Spring	2	Alternative material: D-1,4 according to DIN 2076:1984 (DIN 17223-1:1984)
14	172.11.079-1	Spring	2	spring wire B-3,0 according to DIN 2076:1984 (DIN 17223-1:1984)
15	172.11.154	Spring	3	spring wire C-2,2 according to DIN 2076:1984 (DIN 17223-1:1984)
16	434.11.039-1	Spring	59	spring wire D-1,8 according to DIN 2076:1984 (DIN 17223-1:1984)
17	432.11.105-1	Spring	3	spring wire C-1,6 according to DIN 2076:1984 (DIN 17223-1:1984)
18	432.11.165	Spring	3	spring wire C-1,4 according to DIN 2076:1984 (DIN 17223-1:1984)
19	155.32.121	Spring	3	spring wire B-3,0; C-3,0 according to DIN 2076:1984 (DIN 17223-1:1984)
20	60.49.064	Ring	3	spring wire B-3,0 according to DIN 2076:1984 (DIN 17223-1:1984)
21	175.52.052	Spacer Ring	12	
22	172.52.123	Spring	12	
23	172.52.147	Valve Spring	12	
24	172.52.128	Spring Ring	6	
25	175.52.024	Spring	24	
26	54.15.028-1A or B40.15.028-1A	Spring	4	spring wire B-0,6 DIN 2076:1984 (DIN 17223-1:1984)
27	54.22.032-2 or B40.22.032-2	Spring	3	spring wire B-2,0; C-2,0 according to DIN 2076:1984 (DIN 17223-1:1984)
28	54.34.148 or B40.34.148	Spring	3	spring wire B-1,6 according to DIN 2076:1984 (DIN 17223-1:1984)
29	172.61.064	Spring	3	spring wire B-1,4 according to DIN 2076:1984 (DIN 17223-1:1984)
30	54.22.011 or B40.22.011	Spring	3	spring wire B-1,2; D-1,2 according to DIN 2076:1984 (DIN 17223-1:1984)
31	172.63.140	Spring	3	wire IIA-1,8 according to GOST 9389-75
32	175.63.025	Spring	3	bar 60S2A-G-HN-6,0 according to GOST 14963-78
33	175.63.049	Spring	2	spring wire B-4,0 according to DIN 2076:1984 (DIN 17223-1:1984)
34	175.63.092	Spring	3	spring wire B-2,2 according to DIN 2076:1984 (DIN 17223-1:1984)
35	432.63.199	Spring	3	spring wire C-2,2 according to DIN 2076:1984 (DIN 17223-1:1984)
36	432.63.200-2	Spring	3	bar 51HFA-B-P-HN-2,5 according to GOST 14963-78
37	B71.70.014	Spring	3	SPRING WIRE B-5,0 (DIN 2076:1984) (DIN 17223-1:1984)
38	B40.35.042	Spring for Retainer	2	spring wire B-1,2 according to DIN 2076:1984 (DIN 17223-1:1984)