



ALLOWABLE DEVIATIONS FOR MACHINING DIMENSION WITHOUT SPECIFIED TOLERANCES IN mm		RANGE	0	6	30	120	315	1000	2000	4000
		TOLERANCE	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2	± 3
REVISION	DATE	CHANGES	BY/APP.	REVISION	DATE	CHANGES	BY/APP.			
△ ^x				△ ^x						

SURFACE TEXTURE
UNLESS OTHERWISE SPECIFIED

TECHNICAL REQUIREMENT

TYPE: PROTECTED TYPE, NON REVERSIBLE WITH SCRAPING EARTH CONTACTS

RATING: 30A

MAKE: M/S. CROMPTON TYPE, BS30 OR EQUIVALENT

CONTROLLED COPY

ITEM REF	QTY.	DRAWING/STOCK NO.	DESCRIPTION	
MATERIAL		SURFACE TREATMENT/PROTECTION		
APPROVED	<i>[Signature]</i>		PRODUCT	SCALE
CHECKED	<i>[Signature]</i>		AC/EMU	1:1
DRAWN	<i>[Signature]</i>	AC/EMU EMU/M2-7-1-501	QTY	1
TRACED		MODEL	NEXT ASSY.	REF.DRG.
STANDARDS		STOCK No.	39429836910101	
BHARAT EARTH MOVERS LTD.		TITLE		Wt. Kg.
bend BANGALORE COMPLEX		BATTERY CHRGING SOCKET 30A		SHEET OF
		DWG. No.		ALT.
		906-21149		△