



SI no.	Description	Supplier Response		
	Drivers Cabin should be provided with 4 doors for the entry and egress of following members			
	1. Driver			
	2. Co Driver			
	Crew Entry LH side			
	Crew Entry RH side			
	Each Door should be equipped with major items having following features			
	1. Fixed Armoured glass			
	2. Suitable door locking mechanism as per CMVR requirements			
	3. Handles on the door for Firm Holding			
	4. Door Hinges as per CMVR requirements			
	5. Pockets for storing water bottles ( 2 nos. 1 ltrs each)			
	6. Cigarette ash tray ( 1 no)			
	7. Suitable sealing on the door panel to prevent water ingress, dust ingress			
	8. Door Panels should be reinforced to withstand blast pressure as per STANAG 1			
	9. Door panels should be covered with armored steel plates with proper bolt on mounting provision			
	10. Inner surface of the door to be provided with ABS trims and suitable sound / vibration damping materials.			
	11.Suitable footsteps for entry of crew			
	The corner fastenings of the front glass are protected with strips against possible damage due to branches of trees. The cabin is sealed against entry of dust and water. There are two hinged screens on top of the front glass for screening against sunlight. There is a manhole in the roof which could be closed. The lid of the manhole is held against a spring stop in the open position and clamped by a bolt in the closed position.			
4	CABIN MOUNTING:			
	Mounting of the swing cabin onto the frame is done using sleeves in the front and prismatic rubber at the rear. Clamping of the cabin in the running condition is done by a control mechanism from the left side			
	The cab lock release mechanism has to be of mechanical linkages arrangement (Tie-rod & Lever to secure the Cabin). Hydraulic system for tilting mechanism of the cabin and Cabin mountings with lock arrangement to be provided			
	The cab lock release mechanism has to be of mechanical linkages arrangement (Tie-rod & Lever to secure the Cabin). Hydraulic system for tilting mechanism of the cabin and Cabin mountings with lock arrangement to be provided.			
	Mechanical stay will be provided in case of failure of Hydraulic system for tilting mechanism			