



MACHINING DEVIATIONS FOR LINEAR DIMENSIONS									THE REST	---
ABOVE UP TO AND INCLUDING	— 6	6 30	30 120	120 315	315 1000	1000 2000	2000 4000	4000 —		
VALUE	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3		

SCOPE: COMPACT GENERAL PURPOSE 40A RELAY FOR DRIVING INDUCTIVE LOAD IN AUTOMOTIVE APPLICATION IS REQUIRED.

SPECIFICATIONS:

RATED COIL VOLTAGE : 12VDC  
 OPERATING VOLTAGE : 7.2V DC TO 14V DC  
 CONTACT RATING : 40 AMPS  
 CONTACT ARRANGEMENT : 1 FORM C  
 TERMINALS : QUICK CONTACT 6.3x0.8mm  
 OPERATING TEMPERATURE : -25°C TO +85°C  
 WITH/WITHOUT BRACKET : WITH BRACKET  
 WITH/WITHOUT DIODE : WITH DIODE  
 MAKE : M/S. OEN INDIA LIMITED  
 MODEL : 741-12-1C-2SCBE

NOTE: THE RELAY SHOULD HAVE ARC SUPPRESSION FEATURE TO PROTECT THE CONTACTS FROM HEAVY INDUCTIVE LOAD/BACK EMF.

NEXT ASSY. 1923CGDK101B						PRODUCT <b>BACK-HOE LOADER</b>		DESIGN REF. ---	
				USED ON	QTY	MATL: ---			
				BL9H		H.T. ---			
						S.T. ---			
374000	AMEND	NO.	SIGNATURE	DATE	TITLE <b>RELAY 12V</b>		Wt. in kg ---		SCALE NTS
DRA/ECN	NAME						SHEET NO.		1
APPROVED	SURESH H.G.			01062024			NO. OF SHEETS		1
REVIEWED									
CHECKED	DEEPAKRAJ			01062024					
DRAWN	SARVESH			01062024					
STDS.	SARVESH			01062024					
						BEML LIMITED KGF		DRG. NO. <b>1923CGDG011D</b>	