

ANNEXURE - B

BERGA CLASSIC PREPRINT

MULTIFUNCTIONAL PREPRINT PAPER

Woodfree uncoated paper for offset printing presses and subsequent personalisation in laser printers.
* Designed for multiple needs : from constat forms to A4 letter heads
* Good runnability in converting, laser, inkjet, plotter, automatic inserting
* Good printability in 3/4 color printing

Typical end uses	Printing method	Converting	Post printing process
Letterheads	UV-Offset	Reel-to-A4	Laser
Direct mail	Cold Set Web Offset	Reel-to-reel	Inkjet
Technical manuals	Plain Paper Copiers	Reel-to-fanfold	Automatic Inserting
Invoices			OCR
Statements			Plotter

Technical Specifications

Substance	g/m²	70	75	80	90	100	115
Bulk	cm ³ /g	1.3	1.3	1.3	1.3	1.3	1.3
Brightness with D65	%	109	109	109	109	109	109
Whiteness CIE	%	163	163	163	163	163	163
Opacity ISO	%	92	93	95	96	97	98
Roughness Bendsten	ml/min	280	300	300	320	340	350
Moisture	%	4.5	4.5	4.5	4.5	4.5	4.5

Reel Specifications	Min. Width	Max. Width	Diameters
	210 mm	2600 mm	1000 and 1200 mm

Core 70, 76, 151 mm

Storage and Handling

* Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19° C and 23°C
* If the paper is stored in non air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room
* Open the protective wrapping at the moment of use

Environment	Certificates	Producer
Renewal Fibre Recyclable Paper Recyclable Packaging Materials	ISO 9001 ISO 14001 OHSAS 18001 EMAS FSC CoC PEFC Coc	Varkaus Mill