

Sub:- Cubical cells required for rest of the Hall Area for ADMIN,Personel Dept. along Over Head File Cabinet having wood finish material with (PLYWOOD/MDF)					
Schudule Bill of Quantities					
SI No	Description of work	Unit	Qty.	Rate/ Unit	Amount
1	<p>Supplying and Placing in Potition of modular workstation -non sharing model: 65 series-linear , sku : 65/1 whole cluster size : 1200mm(l)x 600mm(d)x 1200mm(h). Non sharing single seater workstation of 67mm thk sliding tile base partition of 1200mm height.Non-sharing single unit workstation table in completely knock down conditions with an overall size 1200mm x 600mm x 1200mm that is to be assembled at site. the work top shall have the size 1184mm x 592mm made up of 25mm thick prelaminated particle board (reputed make like godrej interior/equivalent) of grade ii type iii of is 12823/latest of is level with approved laminate and finish as per approved shade. The profile of the top shall be in rectangle shape and the edges shall be sealed with 2mm thick thin strip of impermeable pvc that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree celsius. The top trim, top bar, mid bar, vertical bar, raceway, skirting shall be made up of aluminium extrusions (pre-treated) and duly powder coated with polyester powder coating 40p-60p thick . the trims shall have the size 67mm x 19mm with 1.5mm thick covered with die cast end caps on joints 2 ways, 3 ways & 4 ways (l-cover for corner, t-cover for middle section wherever required). the aluminium raceway shall be situated below the worktop with an overall size 116mm(h) x 60mm(d) with 1.4 mm cover thickness and 2mm back thickness as per requirement of inlaying the electrical management and carrying the wire horizontally.The exposed vertical and horizontal faces of the frames shall be snap fitted with trims. there shall be soft-board (with fabric) and marker board provided at front of the user. laminated top tile and bottom tile shall be situated at both sides of the user and below the work top respectively. the partition shall have concealed wire management capabilities and should be engaged for responsive and safe operations of power, telecommunications and data (lan) and has separate components for electrical, data and telephone cables having adequate capability of both the vertical and horizontal wire movements. slots/cut-outs should be given on raceways to fix all electrical and data points. single sided pvc wire manager should be enclosed at table top.adjustable leveller shoe shall be provided at bottom of the partition to avoid scratches on the floor.particle board of grade ii of is level. Providing and 400L x 450W x 725Ht Fixed Pedestal of 2 Drawer + 1 Filling unit, made of 18mm thk pre- laminated particle board with PVC edge banding. All drawers shall have a central lock mechanism. MS powder coated cpu trolley with castors. Pvc keyboard tray. Three layer prelaminated particles board (wood product) of grade ii type iii of is 12823/latest .The Seller/Company should be NABCB CERTIFIED ISO-9001:2008, ISO-9001:2015, ISO14001:2015, OHSAS-18001:2007. OTHER CERTIFICATIONS : Green pro, Indian Design Mark, AIOTA, FSC & PEFC certified. The Bidder should also be a member of BIFMA and One or more products of the OEM should be certified as BIFMA LEVEL compliant and an official link/screenshot of the product listing must be provided from www.bifma.org”</p>	Nos.	8		
2	<p>Supplying and placing in position of medium back 360° degre revolving chair sku : nature/MB/PREMIUM . All over size is : 630mm(L) x 675mm (D) x 1115mm(H) ,The chair made of full mesh in black colour.It will comes in matte finsih in contemporary style .Details :- Arms : amrest is having two adjustment heights (up & down), Use of ply: 12 mm thick hot pressed bwr plywood (is grade - 303 for seat). Seat: 40 ± 2 mm thick polyurethane foam with density 32 (±3) kg per cu meter for best quality cushioning in seat , Back : frame of design shall be curved made of two pieces injection moulded frame cover with mesh .backrest support adjustable lumbar support ; Mechanism : self weighted multi locking mechanism .Only seat size is 520mm (L) x 525mm (D) x 445-545mm (H) & the back size is 470mm (L) x 590mm (H) , Seat maximum height is 545mm & minimum height is 445mm & back height from floor maximum height is 1115mm & minimum height is 1015mm. Gas lift 100 mm telescopic haudraulic and base : 650 mm chrome base with smooth castors . The Seller/Company should be NABCB CERTIFIED ISO-9001:2008, ISO-9001:2015, ISO-14001:2015, OHSAS-18001:2007.OTHER CERTIFICATIONS : Green pro, Indian Design Mark, AIOTA, FSC & PEFC certified. The Bidder should also be a member of BIFMA and One or more products of the OEM should be certified as BIFMA LEVEL compliant and an official link / screenshot of the product listing must be provided from www.bifma.org</p>	Nos.	6		
3	<p>Supplying and placing in position of overhead storage size: 1050mm length x 450mm depth x 600mm height. Top is made of 18mm thick pre-laminated particle board (reputed make like godrej interior/equivalent) with 2mm thick pvc edge banding and the rest carcass is of 18mm thick while back shall be 9mm thik pre laminated particle board. The storage contains equally divided openable shutters, handles & lock. The working or nonworking edges shall be provided with matching machine pressed 2mm thick pvc edging using with special hot melt glue at hot temperature. Overhead supported wall side only. The Seller / Company should be NABCB CERTIFIED ISO-9001:2008, ISO 9001:2015, ISO -14001:2015, OHSAS-18001:2007. OTHER CERTIFICATIONS :Green pro, Indian Design Mark, AIOTA, FSC & SEDEX. The Bidder should also be a member of BIFMA and One or more products of the OEM should be certified as BIFMA compliant and an official link/screenshot of the product listing must be provided from www.bifma.org</p>	Nos.	4		