

BEML LIMITED, BANGALORE COMPLEX

Ref: 6300036087

Date: 12.06.2021

ISSUED TO:	Period of contract:	45 Days
	EMD :	Rs. 2,140/-

Sub: Providing Anodized Aluminum Partition in Cable Harness area of Hangar 5, Bangalore Complex BEML Limited, Bangalore-75.

SCHEDULE 'A' - BILL OF QUANTITIES

Sl. No	Description	Unit	Qty	Rate/unit in fig. & in words Rs.	Amount (Rs)
1	<p>Supplying and fixing/installing new powder coated aluminium partitions of approximate height 3.0 m using standard aluminium sections manufactured by M/s. Jindal/ Hindalco/ Indal/ equivalent make, conforming to relevant IS, comprising of rectangular hollow tubes measuring not less than 63.5mm x 38.10mm x 2.50mm for outer frame, verticals and horizontals. The minimum thickness of the powder coating shall be 50 microns. The centre to centre distance between the vertical members shall not be more than 1.2 m approximately.</p> <p>The bottom and top panels of the partition shall have a height of 0.95 m approximately and shall be fixed with 12mm thick both sides decorative prelaminate particle board of approved colour and shade conforming to relevant IS manufactured by M/s.Archid/ Kitply/ National/Greenply.</p> <p>The middle panel of the partition for an approximate height of 1.10 m shall be fixed with 5mm thick plain / frosted glass conforming to relevant IS manufactured by M/s. Modiguard / SaintGobain, including necessary hardware and accessories viz., EPDM rubber / neoprene gaskets, snap beading, aluminium glazing clips, screws, etc., complete as per site conditions and all as specified and directed by Engineer in charge.</p>	Sqm	35.00		
2	<p>Supplying and fixing new powder coated aluminium single leaf openable door of approximate height 2.10 m using standard sections manufactured by M/s. Jindal/ Hindalco/ Indal/ equivalent make, conforming to relevant IS.</p> <p>The top, middle and side members shall comprise of sections measuring not less than 50mm x 44.50mm x 2.50mm. The bottom panel shall comprise of sections measuring not less than 101.60mm x 44.45mm x 2.50mm. The minimum thickness of the powder coating shall be 50 microns.</p> <p>The bottom panel of the door for a height of 0.95 m approximately shall be fixed with 12mm thick both sides decorative prelaminate particle board of approved colour and shade conforming to relevant IS manufactured by M/s.Archid/Kitply/ National/Greenply.</p> <p>The top panel of the door for an approximate height of 1.10 m shall be fixed with 5mm thick plain / frosted glass conforming to relevant IS manufactured by M/s. Modiguard/ Saint Gobain, including necessary hardware and accessories viz., EPDM rubber / neoprene gaskets, snap beading, aluminium glazing clips, screws, handles, locking arrangement, floor spring of approved brand manufactured by M/s. Dorma/Everite/Hardwyn etc., complete as per site conditions and all as specified and directed by Engineer in charge.</p>	Sqm	2.25		
	Note:				
	(1) Interested bidders/contractors are requested to visit the site and acquaint themselves with the site conditions before submission of their quote/offer for the work.				
	(2) The rate quoted by the bidders/contractors is deemed to include for (a) providing & removal of scaffolding/staging wherever required for the work under the relevant item. (b) Wastages.				
	Total value of work excluding GST			Rs.	
	GST Amount			Rs.	
	Total value of work inclusive of GST			Rs.	

Total Amount in words Rupees_____

Signature of the Contractor
with seal